

1/22




FIG. 1A




FIG. 1B




FIG. 1C

3/22




FIG. 2A

4/22




FIG. 2B












FIG. 2C

5/22



6/22



7/22

## Filter Arrangement




FIG. 6

8/22

Alternative Filter Arrangement




FIG. 7




FIG. 8



9/22




FIG. 9

Plan View

PC or IC

Various X2Y' Arrangements




FIG. 10

10/22

Plan View, Partial Section

PC board or CPU with multiple lines or waveguides  
for "high frequency" operation.





FIG. 11

11/22

Plan View, Partial Section

PC board or CPU with multiple lines or waveguides  
for "high frequency" operation.



X2Y' structure in various configurations  
and number; some spanning at least 2 lines.  
Preferably, one differential electrode per  
line spanned.

FIG. 12

12/22




FIG. 13A




FIG. 13B

13/22




FIG. 14




FIG. 15

14/22




FIG. 16




FIG. 17




FIG. 18

15/22




FIG. 19A




FIG. 19B

16/22




FIG. 20A




FIG. 20B



17/22




FIG. 21




FIG. 22

18/22




FIG. 23A




FIG. 23B

19/22




FIG. 23C




FIG. 24

Side View




FIG. 25A

Side  
Sectional  
View




FIG. 25B




FIG. 25C

21/22




FIG. 26A




FIG. 26B

22/22




FIG. 27